

TYLÖ®



S A U N A S

S H O W E R S

S T E A M B A T H S

Steam bath accessories.



Steam Guard

Steam Guard W (Art. 9002 9210)

For wall installation inside the steam room to protect bathers from the hot jet of steam. Recommended in all public facilities.

Steam Guard 778 (Art. 9002 9220)

As above, but for 778 mm section in Tylö Elysée steam rooms.

Steam Guard 588 (Art. 9002 9230)

As above, for 588 mm section.

Steam Guard Corner

(Art. 9002 9240)

As above, for corner section.



Optical fibre lighting

Halogen lighting for atmospheric lighting in all sorts of settings. The lighting source is in a projector placed outside the sauna room. The length of the optical fibres determines the maximum distance between the projector and the light points.

Fiber Light Standard

(Art. 9001 1100)

42 W with 6 light points (2 x 2 m, 2 x 2.5 m and 2 x 3 m).

Fiber Light Public (Art. 9001 1120)

42 W with gilded fittings and 8 light points (2 x 2.5 m, 3 x 3 m and 3 x 3.5 m).

Fiber Light Colour S (Art. 9001 1125)

75 W with 9 light points (1 x 0.5 m, 2 x 1 m, 3 x 1.6 m, 2 x 1.9 m, 1 x 2.3 m) and a rotating disc for fixed or changing colours.

Fiber Light Colour (Art. 9001 1130)

75 W, as above but with 9 light points on 2.5 metre cables for large rooms.



Downlight (Art. 9001 1081)

Effective spotlighting for installation in the steam room. 12 V/5 W. Connect to our 12 V transformer below.

Transformator 12 V/210 W

(Art. 9090 1015)

200–240 V~/12 V max. 210 W.

Transformator 12 V/60 W

(Art. 9090 1020)

As above, but for max. 60 W.



Lighting strips

May be cut to size and installed under the benches in Excellent steam rooms. 12 V. Connect to our 12 V transformer.

Lighting strip 38 (Art. 9001 1040)

Length 38 cm. 12 W.

Lighting strip 50 (Art. 9001 1050)

Length 50 cm. 15 W.

Lighting strip 90 (Art. 9001 1060)

Length 90 cm. 27 W.

Lighting strip 190 (Art. 9001 1070)

Length 190 cm. 57 W.



Service section, complete

(Art. 4990 5085)

Wall section in white, vacuum-formed, special-grade plastic. Jet nozzles for water massage, thermostatically controlled mixer tap, shower head, riser rail and soap/shampoo compartments. May be used to replace a wall/seat section.

Service section (Art. 4990 5081)

As above, but without jet nozzles.



Fragrance dispensers

Tylö Fresh (Art. 9090 8005)

Fragrance dispenser for saunas, steam baths and wherever else Tylö's aromatic essences may be needed. Silent, automatic operation. Installation distance: max. 2 metres between fragrance dispenser and nozzle. Up to four fragrance dispensers may be connected to a single control panel for varying the fragrance in one or more rooms. Size: 350 x 200 mm.

CC Fresh (Art. 9090 8006)

Electronic control panel for easy, automatic operation of Tylö Fresh dispenser. Supplied complete with transformer. May be installed at any distance from the fragrance dispenser. Size: 130 x 190 mm, depth 27 mm.

Tylö Fresh Basic (Art. 9090 8007)

As Tylö Fresh above, but with transformer and simple on/off function for manual control of the fragrance intensity. May also be connected to lighting, etc. For domestic saunas only.



Steam jet

Steam Outlet (Art. 9002 9205)

Steam head with integral dispenser for Tylö fragrances. Connect to the steam generator's steam pipe.

Descaling agent

Sulfamic solvent (Art. 9090 3010)

An extra effective descaling agent for professional use only in public facilities. Sold in a 5-kilo pack.

Solvent 50 (Art. 9090 3007)

Powder for descaling the water tank in Tylö steam generators. Totally odourless and harmless. Sold in packs of 50.



Loudspeaker A (Art. 9080 2000)

Steam and heat-resistant materials suitable for recessed installation inside the steam room. 50 W output. Installation size: 120 mm diameter, depth 55 mm.

Loudspeaker B (Art. 9080 3000)

As above, 50 W, but for surface-mounting. Size: 77 x 114 mm, depth 125 mm.

Disinfecting equipment



Steam Clean (Art. 9090 8020)

For automatic day-to-day hygiene and disinfection of steam rooms in hotels and public facilities, etc. One hour after completion of the bathing cycle the entire room is automatically flushed with water. A ceiling-mounted sprinkler sprays disinfectant throughout the room and then repeatedly rinses it off with clean water. A security code function ensures that the disinfecting cycle can not be activated accidentally. Steam Clean is indispensable in all public facilities.



Disinfectant (Art. 9002 9100)

Disinfecting liquid for use with Steam Clean (above). Supplied in a 5-litre plastic container.

Registered office, factory and warehouse:
Svarvaregatan 6, SE-302 50 Halmstad, Sweden
Tel: +46 35-299 00 00 • Fax: +46 35-299 01 98
E-mail: info@tylo.se • Website: www.tylo.com

TYLÖ®
www.tylo.com